





## Feature

Suitable for wall mounting:	Yes	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for suspended mounting:	Yes	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for ceiling mounting:	Yes	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for built-in mounting:	Yes	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for surface mounting:	Yes	Degree of protection (IP):	IP20
Suitable for light line configuration:	No	Degree of protection (NEMA):	1
Suitable for workplace according to EN 12464-1:	Yes	Impact strength:	IK02
Lamp type:	LED not exchangeable	Protection class:	II
With light source:	Yes	Luminaire with limited surface temperature, sign "D":	No
Lamp holder:	Other	Rated ambient temperature according to IEC62722-2-1:	-20 ~ 40 °C
Material housing:	Aluminium	Suitable for emergency lighting:	Yes
Surface protection housing:	Powder coating	Emergency power supply integrated:	No
Colour housing:	White	With movement sensor:	No
Material cover:	Other	With light sensor:	No
Type of grid:	None	Covering of the luminaire with thermally insulating material possible:	No
Voltage type:	AC	With air slots:	No
Nominal voltage:	220 ~ 240 V	Filament test according to IEC 60695-2-11:	650 °C - 30 s
Nominal current:	117 ~ 117 mA	Suitable for lamp power:	0 ~ 0 W
Type of control gear:	LED operating device current-controlled	Max. system power:	27 W
With control gear:	Yes	Luminaire efficacy:	130 lm/W
Exchangeable control gear:	No	Rated luminous flux according to IEC 62722-2-1:	3510 lm
Dimming 0-10 V:	No	Colour of light:	White
Dimming 1-10 V:	No	Colour temperature:	3000 ~ 5700 K
Dimming DALI-2:	No	Flickering value Pst LM:	0.01
Dimming DALI:	No	Colour rendering index CRI:	80-89
Dimming DMX:	No	Power factor:	0.9
Dimming DSI:	No	Stroboscope effect value SVM:	0.03
Dimming potentiometer (integrated):	No	Constant light output (CLO):	No
Dimming GPRS:	No	Width:	595 mm
Dimming LineSwitch:	No	Height/depth:	16 mm
Dimming manufacturer's proprietary system:	No	Length:	595 mm
Dimming mains voltage modulation:	No	Outer diameter:	0 mm
Dimming phase cut-off:	No	Built-in length:	595 mm
Dimming phase cut-on:	No	Built-in width:	595 mm
Dimming programmable:	No	Built-in height/depth:	16 mm
Dimming RF:	No	Built-in diameter:	0 mm
Dimming Sine Wave Reduction:	No	Type of wiring:	Ending
Dimming Touch and Dim:	No	Number of poles:	2
Dimming Zigbee:	No	Conductor cross section:	0.75 mm <sup>2</sup>
Dimming with push-button:	No	Connection type:	Other
Dimming depending on control gear:	No	Total harmonic distortion:	12
No dim function:	Yes	Photobiological safety according to EN 62471:	RG0
Light distributor:	Reflector	Unified Glare Ratio (UGR):	17
Light sharing:	Symmetric	Luminous intensity:	0 cd
Beam angle:	Wide beam 41-80°	Colour temperature adjustable:	Positions



Colour consistency (McAdam ellipse):	SDCM6	Luminous flux adjustable:	No
Light outlet:	Direct/indirect	Beam angle adjustable:	No
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Operation by Bluetooth:	No
Rated life time L70/B50 at 25 °C:	83000 h	Compatible with Apple HomeKit:	No
Rated life time L80/B10 at 25 °C:	0 h	Compatible with Google Assistant:	No
Rated life time L90/B10 at 25 °C:	0 h	Compatible with Amazon Alexa:	No
Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %	IFTTT support available:	No
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %		

## Packaging data

Weight	3.38 kg
Width	669 mm
Height	48 mm
Length	646 mm
Customs code	9405119090

