

Eurostar Fire Fighting Hose EUROSTAR Coated (Grizzly)



Robust DIN Fire hose Class 2

Robust fire hose with a red polyurethane outer coating. Manufactured from 100% synthetic polyester yarn, round-woven in twill weave. Inner rubber lining manufactured using a two-layer process from extremely age-resistant EPDM.

Advantages

- Very light and flexible
- Compact
- Increased abrasion resistance and flame retardancy
- Enhanced resistance to oil and petrol
- Rot-proof
- Cold-resistant down to -40°C
- Heat-resistant up to +100°C
- Easy to care for and maintenance-free

Approvals

- DIN 14811 Class 2
- ÖNORM F 2106
- BS 6391 Type II
- Russian Maritime Register

Services

- Custom labelling available
- Complete hose assembly with international couplings
- Other hose diameters available on request
- Available in lengths of up to 1,000 m, depending on diameter

Article code RED	Diameter Inch (mm)	Weight (g/m)	Burst pressure (bar)	Working pressure (bar)	Test pressure (bar)
ERMC0250	1" (25)	130	60	16	24
ERMC0320	1.1/4" (32)*	175	60	16	24
ERMC0380	1.1/2" (38)*	205	60	16	24
ERMC0450	1.3/4" (45)*	260	60	16	24
ERMC0500	2" (52)	285	60	16	24
ERMC0650	2.1/2" (65)*	355	60	16	24
ERMC0700	2.3/4" (70)*	385	60	16	24
ERMC0750	3" (75)	485	60	16	24

* On demand