

RIG SUPPLY SW

Premium layflat bunker hose



Suitable for dock loading and as a supply hose for offshore drilling rigs

- Suitable for hydrocarbons up to 55% aromatics, solids, mud, barite, cement and diesel
- 4 high tensile cord plies with 2 antistatic wires
- High abrasion and oil resistant cover
- Suitable for use on hose reels
- Cover flame resistant according U.S. MSHA norm
- Elongation at 17 Bar < 4%, max. end load at break 6,5 tons
- Not suitable for ship-to-ship applications (!)

Branding **CONTINENTAL CONTITECH RIG SUPPLY SW WP 20BAR - M MADE IN CANADA**

Temp. Min °C	Temp. Max °C	Working pressure bar	Burst pressure bar	Length M
-35	+93	16 / 20	64 / 60	30.5 / 61 / 122

Article no.	Inner ø mm	Outer ø mm	Bending radius mm	Vacuum bar	Weight gr/m	Work Pressure bar	Burst Pressure bar
AOBF076	76.2	90.0	457	0	2700	20	60
AOBF102	101.6	116.0	660	0	3870	20	60
AOBF127	127.0	143.0	762	0	4760	20	60
AOBF152	152.4	172.0	900	0	5770	16	64
AOBF203	203.2	223.0	1200	0	8540	20	60
AOBF254	254.0	280.0	1500	0	13940	20	60