

SILOCORD®



Dry cargo discharge hose
for cement, dry plaster, cattle food and other abrasive materials.
Marking: Silocord® Zement / Dry Cargo – PN 8 bar – M

Norm	EN ISO 1307:2008 / ISO 4649 (previous DIN 53516)
WP	8 bar
BP	24 bar
Min. temperature	-30 °C
Max. temperature	+80 °C
Electr. resistance tube	Electrical conductive $<10^6 \Omega$
Electr. resistance cover	Electrical conductive $<10^6 \Omega$
Compound tube	NR/SBR
Abrasion value tube	90-110 mm ³
Construction tube	Smooth
Color tube	Black
Compound cover	SBR
Construction cover	Fabric finish
Color cover	Black
Reinforcements	Textile plies / Static wire

Art.no.	Ø Inner mm	Wall mm	Ø Outer mm	Bendingradius mm	Weigth mtr	Length mtr
ACEDU075	76	9,0	94	760	2,870 kg	20/40
ACEDU076	76	11,0	98	760	3,640 kg	40
ACEDU080	80	10,0	100	800	3,400 kg	40
ACEDU090	90	10,0	110	900	3,780 kg	20/40
ACEDU100	102	10,0	122	1020	4,240 kg	20/40

Application:

Very wear resistant and flexible silo hose that can be used for filling and unloading silos and silo trucks. Suitable for highly abrasive materials such as cement, sand, lime powder, animal feed, granulates, wood pellets etc. The hose is very easy to handle due to its flexible construction. It is one of the safest hoses for this application as the static electricity will be discharged through the static wire and the rubber itself also has conductive properties.