

VACUFLEX®



This Vacuflex hose features a soft PVC wall, Shore A-70, welded to a PVC-sheathed spring steel coil. The coil pitch is left-handed.

It is a flexible and lightweight hose with a slightly corrugated inner wall. The hose has excellent mechanical properties. This hose is universally applicable as a ventilation and deaeration hose and as a material transport hose in the textile, wood, plastics, and chemical industries. The hose is also used as a protective hose for cables in machine and equipment manufacturing and electrical engineering, and in the automotive and yacht building industries as a ventilation and heater hose.

Minimum order quantities apply to this hose or to specific diameters.

A number of diameters are also available in 5-meter rolls.

If you do not enter a roll length, we will assume 10 meters.

Technical data:

Color: Black

Temperature range: -10 to +70°C

Part no.	I.D.	Underpressure	Bendingradius	Overpressure	Length
CAFVA010	10 mm	350 mbar	10 mm	0,5 bar	10 mtr
CAFVA012	12 mm	350 mbar	12 mm	0,5 bar	10 mtr
CAFVA014	14 mm	350 mbar	14 mm	0,5 bar	10 mtr
CAFVA016	16 mm	350 mbar	16 mm	0,5 bar	10 mtr
CAFVA018	18 mm	350 mbar	18 mm	0,5 bar	10 mtr
CAFVA020	20 mm	350 mbar	20 mm	0,5 bar	10 mtr
CAFVA022	22 mm	350 mbar	22 mm	0,5 bar	10 mtr
CAFVA024	24 mm	350 mbar	24 mm	0,5 bar	10 mtr
CAFVA025	25 mm	300 mbar	25 mm	0,5 bar	10 mtr
CAFVA026	26 mm	300 mbar	26 mm	0,5 bar	10 mtr
CAFVA028	28 mm	300 mbar	28 mm	0,5 bar	10 mtr
CAFVA030	30 mm	300 mbar	30 mm	0,5 bar	10 mtr
CAFVA032	32 mm	300 mbar	32 mm	0,5 bar	10 mtr
CAFVA035	35 mm	300 mbar	35 mm	0,5 bar	10 mtr
CAFVA038	38 mm	300 mbar	38 mm	0,5 bar	10 mtr
CAFVA041	41 mm	300 mbar	40 mm	0,5 bar	10 mtr
CAFVA045	45 mm	300 mbar	45 mm	0,5 bar	10 mtr
CAFVA048	48 mm	300 mbar	48 mm	0,5 bar	10 mtr
CAFVA050	51 mm	250 mbar	51 mm	0,4 bar	10 mtr
CAFVA053	53 mm	250 mbar	53 mm	0,4 bar	10 mtr
CAFVA055	55 mm	250 mbar	55 mm	0,4 bar	10 mtr
CAFVA057	57 mm	250 mbar	57 mm	0,4 bar	10 mtr
CAFVA060	60 mm	250 mbar	60 mm	0,4 bar	10 mtr
CAFVA063	63 mm	250 mbar	63 mm	0,4 bar	10 mtr
CAFVA065	65 mm	250 mbar	65 mm	0,4 bar	10 mtr
CAFVA070	70 mm	250 mbar	70 mm	0,4 bar	10 mtr
CAFVA075	76 mm	250 mbar	76 mm	0,4 bar	10 mtr
CAFVA082	82 mm	250 mbar	82 mm	0,4 bar	10 mtr
CAFVA090	90 mm	250 mbar	90 mm	0,4 bar	10 mtr
CAFVA0100	102 mm	250 mbar	102 mm	0,4 bar	10 mtr
CAFVA0110	110 mm	250 mbar	130 mm	0,4 bar	10 mtr

CAFVA115	115 mm	250 mbar	145 mm	0,4 bar	10 mtr
CAFVA120	120 mm	250 mbar	150 mm	0,4 bar	10 mtr
CAFVA125	127 mm	250 mbar	175 mm	0,4 bar	10 mtr
CAFVA130	130 mm	120 mbar	180 mm	0,2 bar	10 mtr
CAFVA140	140 mm	120 mbar	185 mm	0,2 bar	10 mtr
CAFVA150	152 mm	120 mbar	190 mm	0,2 bar	10 mtr
CAFVA160	160 mm	120 mbar	195 mm	0,2 bar	10 mtr
CAFVA180	180 mm	120 mbar	220 mm	0,2 bar	10 mtr
CAFVA200	203 mm	50 mbar	250 mm	0,1 bar	10 mtr
CAFVA225	225 mm	50 mbar	300 mm	0,1 bar	10 mtr
CAFVA250	254 mm	50 mbar	330 mm	0.1 bar	10 mtr