

DURASTAR



Inside and outside rubberlined fire hose

Supreme heavy duty lay flat hose for all firefighting operations. Circular woven jacket out of 100% high tenacity synthetic yarn, embedded in a vulcanized high grade Nitrile/PVC compound using the "Through-the-weave-extrusionprocess". Offers high resistance to acids, salt solutions, oil, fuel and many more chemicals.

Advantages

- Lightweight lay flat hose
- Minimum friction loss
- High aging resistance
- Ribs on outside lining for high abrasion resistance
- High resistance to oil, chemicals and fuel
- Excellent resistance to ozone and weathering
- Cold-resistant up to -35°C
- Heat-resistant up to +100°C
- Easy maintenance and handling

Approvals

- DIN 14811 Class 3
- BS 6391:2009 Type III
- Russian Maritime Register

Services

- Standard colour red, other colours on request
- Light ribless version available
- Individual marking available
- Binding with international couplings available on request
- Other diameters on request
- Available in lengths up to 200 m

Article code	Diameter Inch (mm)	Weight (g/m)	Burst pressure (bar)	Working pressure (bar)	Test pressure (bar)
EDURA0250	1"(25)*	180	50	17	24
EDURA0320	1 ¼"(32)*	230	50	17	24
EDURA0380	1 ½"(38)*	310	50	17	24
EDURA0450	1 ¾"(45)*	346	50	17	24
EDURA0500	2"(52)*	410	50	17	24
EDURA0650	2 ½"(65)	580	50	17	24
EDURA0700	2 ¾"(70)	590	50	17	24
EDURA0750	3"(75)	700	50	17	24
EDURA0900	3 ½"(90)	810	40	15	24
EDURA1000	4"(102)	850	40	15	24
EDURA1250	5"(127)	1350	30	10	24
EDURA1500	6"(152)	1600	30	10	24
EDURA2000	8"(203)	3000	30	10	24