

RVS kogelkraan 3-delig



RVS 316 kogelkraan / SS 316 ball valve

3-delig - 2x binnendraad
Draad in conformiteit met ANSI B2.1, BS 12-1973,
DIN259/2999, ISO 228
Blow-out bestendigde stam / Volle doorlaat
Precisiegegoten vorm en kap
69 bar W.O.G.

3-PC ball valve
Pipe thread in accordance with ANSI B2.1, BS 21-1973,
DIN 259/2999, ISO 228
Blow-out proof stem/ Full port
Investment casting body and cap
69 bar W.O.G.

maat inch	dia mm	inbouw- lengte	Part.no:
1/4"	12.8	59	KKO301006
3/8"	12.8	59	KKO301010
1/2"	15	64	KKO301012
3/4"	20	75	KKO301019
1"	25	85	KKO301025
1.1/4"	32	97	KKO301032
1.1/2"	38	110	KKO301038
2"	50	132	KKO301050
2.1/2"	65	167	KKO301065
3"	80	187	KKO301075
4"	100	230	KKO301100

RVS kogelkraan 3-delig las



RVS 316 kogelkraan / SS 316 ball valve

3-delig - 2x binnendraad
Draad in conformiteit met ANSI B2.1, BS 12-1973,
DIN259/2999, ISO 228
Blow-out bestendigde stam / Volle doorlaat
Precisiegegoten vorm en kap
69 bar W.O.G.

3-PC ball valve Butt weld end, socket weld end
Pipe thread in accordance with ANSI B2.1, BS 21-1973,
DIN 259/2999, ISO 228
Blow-out proof stem/ Full port
Investment casting body and cap
69 bar W.O.G.

maat inch	dia mm	inbouw- lengte	Part.no:
1/4"	12.8	59	KKO3L01006
3/8"	12.8	59	KKO3L01010
1/2"	15	64	KKO3L01012
3/4"	20	75	KKO3L01019
1"	25	85	KKO3L01025
1.1/4"	32	97	KKO3L01032
1.1/2"	38	110	KKO3L01038
2"	50	132	KKO3L01050
2.1/2"	65	167	KKO3L01065
3"	80	187	KKO3L01075
4"	100	230	KKO3L01100