

Concrete Pumping Hose 740AA



Concrete pumping 100 bar (1500 psi) - Extra service - Steel reinforced

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile steel cords.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: high pressure concrete pumping. Designed for long service life in heavy duty applications.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

Artikel	ID		OD		WP	BP	Bendradius	Weigth				
	mm	inch	mm	inch				bar	psi	mm	inch	kg/m
A741AA050	51,0	2"	69,00	2,72	100	1500	200	2900	255,0	10,04	2,57	1,73
A741AA065	63,0	2 1/2"	85,00	3,35	100	1500	200	2900	315,0	12,40	3,75	2,53
A741AA075	76,0	3"	100,00	3,94	100	1500	200	2900	380,0	14,96	4,95	3,33
A741AA090	90,0	3 1/2"	116,00	4,57	100	1500	200	2900	450,0	17,72	7,19	4,84
A741AA100	102,0	4"	128,00	5,04	100	1500	200	2900	510,0	20,08	7,63	5,13
A741AA125	127,0	5"	155,00	6,10	100	1500	200	2900	635,0	25,00	10,22	6,87