SILOCORD® / SPECIAL



Dry cargo discharge hose heavy duty quality for highly abrasive materials, silica sand, soda a.o. Tul extremely abrasive resistant.
Marking: Silocord® / Spezial für Splitt – Soda – Quarzsand PN 10 bar – M

Norm	EN ISO 1307:2008 / ISO 4649 (voorheen DIN 53516)
WP	10 bar
BP	30 bar
Min. Temperature	-30 °C
Max. temperature	+85 °C
Electr. resistance tube	Electrical conductive $<10^6$ Ω
Electr. resistance cover	Electrical conductive $<10^6$ Ω
Compound tube	NR
Abrasion value tube	70 mm^3
Construction tube	Smooth
Color tube	Black
Compound cover	NR/SBR
Construction cover	Fabric finish
Color cover	Black
Reinforcements	Textile plies / 2 static wires

Art.no.	Ø Inner mm	Wall mm	Ø Outer mm	Bending radius mm	Weigth mtr	length mtr
ACESZP075	76	11	98	760	3,44 kg	40
ACESZP100	102	12	126	1020	4,85 kg	20

Application: Very wear and notch resistant silo hose that can be used for filling and unloading silos and is extremely suitable for very abrasive materials such as split, soda, quartz sand, etc. Hose has an extra thick wear-resistant tube, which gives it a very good lifespan at heavy duty applications. Hose has a double safety as the static electricity is discharged through the cross-braided static wires and the rubber itself also has conductive properties.
Remark: At assembly connect both static wires.