

Superflex PU R

Suction Hose



The Superflex PU PLUS H is a polyurethane hose with galvanized steel spiral sheathed in PVC for suction and transport of dust, chips and abrasive material.

Specifications

Brand	Superflex
Material	Polyurethane
Colour	Transparent
Min. temperature	-40°C.
Max. temperature	+90 °C.
Working Pressure	0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 1, 1.1, 1.2, 1.3, 1.5, 1.6, 1.8, 2, 2.3, 2.6, 2.8 & 3 bar
Vacuüm	1, 1.5, 1.6, 1.8, 2, 2.5, 3, 3.5, 4, 4.5, 5, 6, 6.5, 7, 7.5 & 8 m/H2O
Length	15 en 30 meter
HS Code	39173900
Country of Origin	Italy

Information

Articlecode	In mm	Out mm	Working bar	Vacuüm m/h2o	Bending Radius mm
CAFVAPUH030	31	38	3	8	65
CAFVAPUH038	39	46	2,8	7,5	75
CAFVAPUH040	41	48	2,6	7	80
CAFVAPUH045	46	53	2,3	6,5	90
CAFVAPUH050	51	58	2	6	100
CAFVAPUH060	61	68	1,8	5	120
CAFVAPUH063	64	71	1,6	5	125
CAFVAPUH070	71	79	1,5	4,5	140
CAFVAPUH076	77	85	1,3	4	150
CAFVAPUH080	81	89	1,2	4	160
CAFVAPUH090	91	99	1,1	3,5	180
CAFVAPUH100	101	110	1	3	200
CAFVAPUH120	121	130	0,8	2,5	240
CAFVAPUH127	128	137	0,8	2,5	250
CAFVAPUH130	131	140	0,8	2,5	260
CAFVAPUH140	141	150	0,7	2	280
CAFVAPUH150	151	160	0,7	2	300
CAFVAPUH160	161	170	0,6	1,8	320
CAFVAPUH180	181	190	0,6	1,6	360
CAFVAPUH200	201	210	0,5	1,5	400
CAFVAPUH250	251	260	0,4	1	500
CAFVAPUH300	301	310	0,3	1	600