

ELECTRIC MOTOR DRIVE

AS0808E (Indoor Use)

- Optimization and match of hydraulic system delivers longer lasting performance
- Optimized electronic control system for better brake ability on a long downhill
- Improved steering mechanism reduces tire wear during turning
- Battery powered with zero emission and environmental-friendly

PRODUCT SPECIFICATION	AS0808E	AS0808
Platform Capacity	230kg	230 kg
Capacity On Deck Extension	113kg	113 kg
Platform Occupants (Indoor)	2	2
Work Height	10m	10 m
Overall Length	2.4m	2.40 m
Overall Width	0.83m	0.83 m
Overall Height - Rails Down	1.95m	1.95 m
Overall Height - Rails Up	2.32m	2.32m
Platform Extension	0.9m	0.9 m
Drive Speed (Lowered/Elevated)	3.5/0.8km/h	3.5/0.8 km/h
Lift / Lower Time	31/40sec	31/40 sec
Gradeability	25%	25%
Max. Slope	1.5°/3°	1.5°/3°
Machine Weight	2,140kg	2,140 kg

Standards Compliance European EN280

HYDRAULIC MOTOR DRIVE

AS0808 (Indoor Use)

- Most durable and reliable scissor stacks
- Reinforced working platform
- Advanced charger with voltage protection
- 4Higher driver comfort and security

