

ELECTRIC MOTOR DRIVE

AS1212E (Indoor Use)

- Optimization and match of hydraulic system delivers longer lasting performance
- Optimized electronic control system for better brake ability on a long downhill
- Improved steering mechanism reduces tire wear during turning
- Battery powered with zero emission and environmental-friendly

PRODUCT SPECIFICATION	AS1212E	AS1212
Platform Capacity	320kg	320 kg
Capacity On Deck Extension	113kg	113 kg
Platform Occupants (Indoor)	2	2
Work Height	14m	14 m
Overall Length	2.47m	2.47 m
Overall Width	1.18m	1.18 m
Overall Height - Rails Down	1.99m	1.99 m
Overall Height - Rails Up	2.56m	2.56m
Platform Extension	0.9m	0.9 m
Drive Speed (Lowered/Elevated)	4/0.8km/h	3.1/0.8 km/h
Lift / Lower Time	58/60sec	65/60 sec
Gradeability	25%	25%
Max. Slope	1.5°/3°	1.5°/3°
Machine Weight	3,300kg	3,300 kg

Standards Compliance European EN280

HYDRAULIC MOTOR DRIVE

AS1212 (Indoor Use)

- Most durable and reliable scissor stacks
- Reinforced working platform
- Advanced charger with voltage protection
- Higher driver comfort and security

