DIESEL RT SCISSOR LIFT

SR1023D (SR3390D) / SR1323D (SR4390D) SR1623D (SR5390D)



HIGHLIGHTS

LGMG SR23D Series rough terrain scissor lifts deliver higher capacities and larger platforms for the most tough construction job sites. Four-wheel drive, oscillating axels and hydraulic outriggers provide superior stability on the most tough uneven surfaces.

- Larger working platform with dual extension decks offers great productivity.
- Powerful diesel engine, oscillating axels and four-wheel drive provide better performance on most rough terrain job sites.
- Standard features with one button auto leveling outriggers, overload system, motion alarm, help the operator to complete the job in a much safer way.
- Pull-out engine tray for easy access and maintenance.
- On-board self-diagnosis system makes it easier for quick troubleshooting.

SPECIFICATIONS

| MODELS | SR1023D(SR3390D) | | SR1323D (SR4390D) | | SR1623D (SR5390D) | |
|---|-----------------------------|------------|-------------------|------------|-------------------|------------|
| Measurements | Metric | US | Metric | US | Metric | US |
| Working Height Max. | 12m | 39.4ft | 15m | 49.2ft | 17.9m | 58.7ft |
| A Platform Height-Raised | 10m | 32.8ft | 13m | 42.65ft | 15.9m | 52.2ft |
| ❸ Platform Height-Stowed | 1.58m | 62ft | 1.83m | 72ft | 2.08m | 81.9ft |
| Platform Length | 3.98m | 13ft | 3.98m | 13ft | 3.98m | 13ft |
| D Platform Width | 1.83m | 6ft | 1.83m | 6ft | 1.83m | 6ft |
| ● Overall Length | 4.9m | 16ft | 4.9m | 16ft | 4.9m | 16ft |
| ⑥ Overall Width | 2.3m | 7.55ft | 2.3m | 7.55ft | 2.3m | 7.55ft |
| ₲ Overall Height-Rails Up | 2.74m | 8.99ft | 2.96m | 9.71ft | 3.18m | 10.45ft |
| Overall Height-Rails Down | 2.06m | 6.75ft | 2.28m | 7.48ft | 2.5m | 8.2ft |
| Extension Deck (Front/Rear) | 1.45/1.14m | 4.75/3.7ft | 1.45/1.14m | 4.75/3.7ft | 1.45/1.14m | 4.75/3.7ft |
| ⊕ Wheelbase | 2.85m | 111.2in | 2.85m | 111.2in | 2.85m | 111.2in |
| Ground Clearance(Ground Clearance-Center) | 0.23m | 0.75ft | 0.23m | 0.75ft | 0.23m | 0.75ft |
| PRODUCTIVITY | | | | | | |
| Platform Occupants Max. (In/out) | 7/7 | 7/7 | 7/7 | 7/7 | 4/4 | 4/4 |
| Platform Capacity | 1100kg | 2430lbs | 910kg | 2010lbs | 680kg | 1500lbs |
| Platform Capacity-Extension | 230kg | 510lbs | 230kg | 510lbs | 230kg | 510lbs |
| Drive Height | 10m | 32.8ft | 8.5m | 27.9ft | 8.5m | 27.9ft |
| Gradeability-Stowed | 40% | | | | | |
| Turning Radius-Outside | 5.33m | 17.45ft | 5.33m | 17.45ft | 5.33m | 17.45ft |
| Raise/Lower Speed | 45/45s 55/55s 55/55s | | | | | S |
| Brakes | Four-wheel Brake | | | | | |
| Drive Mode | 4×4 | | | | | |
| Tires Type | Solid | | | | | |
| Tires Size | 835×290mm | 33×12in | 835×290mm | 33×12in | 835×290mm | 33×12in |
| POWER | | | | | | |
| Power Source | Deutz D2.9 L4 36.4kw/48.8hp | | | | | |
| Fuel Tank Capacity | 110L | 30gal | 110L | 30gal | 110L | 30gal |
| HYDRAULIC SYSTEM | | | | | | |
| Hydraulic Oil Capacity | 140L | 37gal | 140L | 37gal | 140L | 37gal |
| WEIGHT | | | | | | |
| Machine Weight(6.58m platform,CE/ANSI) | 6880kg | 15170lbs | 7360kg | 16230lbs | 8100kg | 17860lbs |
| Machine Weight(7.4m platform,CE/ANSI) | 6980kg | 15400lbs | 7460kg | 16450lbs | 8200kg | 18080lbs |





