

# Ultra-Lok® Clamping System



Ultra-Lok® Free  
End Clamps and  
Buckles

## The stronger and faster alternative to band and buckle

Designed for quick installation, tightest clamping force and gap-free inside diameter. The strongest band clamping system available.

- Smooth inside diameter designed to eliminate leak paths
- Single or double wrapped 1/4 hardened 201SS for superior clamping strength
- Locks under full tension (no slip-back) maximizing clamping force
- Applied four times faster than band and buckle
- Consistent and repeatable tensioning
- Buckle is thicker and 2-3 times stronger than other clamps
- Buckle hood protects lock from snags
- Ideal for field repairs / heavy duty bundling / attachment of Brack-Its and equipment to poles, etc



### UL4000 / UL9010

See pages 26-29 for full details on TOOLS and their specifications.

## Ultra-Lok® Free End Clamps

Type 201 1/4 hardened stainless steel band • Thickness 0.030" (0.76mm)

PART NUMBER	CLAMP DIAMETER				BAND WIDTH		LENGTH		WIDTH		PACKAGE QTY
	SINGLE WRAP		DOUBLE WRAP								
	In	mm	In.	mm	In	mm	In	mm	Lbs	Kg	
UL2030	8.0	203.2	3.8	96.5	3/4	19.05	30	762	5.25	2.39	25
UL2042	11.8	299.7	5.7	144.8	3/4	19.05	42	1067	7.00	3.18	25
UL2060	17.5	444.5	8.6	218.4	3/4	19.05	60	1524	10.25	4.66	25
UL2084	25.2	640.1	12.4	315.0	3/4	19.05	84	2134	14.75	6.70	25
UL2120	36.6	929.6	18.2	462.3	3/4	19.05	120	3048	20.50	9.32	25
UL1018	3.0	76.2	-	-	1/2	12.70	18	457	2.00	0.91	25
UL1024	5.0	127.0	-	-	1/2	12.70	24	610	2.75	1.25	25
UL1028	6.0	152.4	3.0	76.2	1/2	12.70	28	711	3.25	1.48	25
UL1032	7.0	177.8	3.5	88.9	1/2	12.70	32	813	3.50	1.59	25
UL1036	8.0	203.2	4.0	101.6	1/2	12.70	36	914	4.00	1.82	25
UL1046	11.0	279.4	5.5	139.7	1/2	12.70	46	1168	5.90	2.70	25
UL1056	14.0	355.6	7.0	177.8	1/2	12.70	56	1422	7.10	3.20	25
UL1070	18.0	457.2	9.0	228.6	1/2	12.70	70	1778	8.50	3.90	25
UL1086	22.0	558.8	11.0	279.4	1/2	12.70	86	2184	10.20	4.60	25
UL1096	25.0	635.0	12.5	317.5	1/2	12.70	96	2438	11.20	5.10	25
UL1106	28.0	711.2	14.0	355.6	1/2	12.70	106	2692	12.70	5.80	25
UL1116	31.0	787.4	15.5	393.7	1/2	12.70	116	2946	13.30	6.00	25

\* 1/2" Bands will require MO9387 shear plate fitted to UL9010 and UL4000 tools

## Ultra-Lok® Free End Buckles

201 Stainless Steel • Pack Qty – 100

PART NUMBER	WIDTH		WEIGHT	
	IN.	MM	LBS	KGS
UB2549	1/2	12.70	2.4	1.1
UB2569	3/4	19.05	3.7	1.7