

MI SERIES SS321 HSQ HEATING CABLE



nVent RAYCHEM HSQ stainless steel (321) sheathed mineral insulated (MI) series resistance trace heating cables provide freeze protection and process temperature maintenance. They can be used for exposure temperatures up to 700 °C (joint dependent) and typical power outputs up to 150 W/m. 321 stainless steel sheath offers high corrosion resistance to a wide range of organic acids and alkalis. Approved for use in hazardous areas. Available 'fast track' as configured heating units.

FEATURES & BENEFITS

Reduced total installed cost Reduced power supply costs: lower start up currents compared with other technologies Simple controls: current monitoring on series resistance provides instant visibility on critical circuits Fast track/expedited service for configured heating units for eligible designs Standard 550 °C continuous withstand temperature, with braze weld technology Optional 700 °C continuous withstand temperature, with laser welded technology High corrosion resistance to a wide range of organic acids and alkalis

SPECIFICATIONS

Supply Voltage 0 – 500 V Max Power Output 150 W/m Max Continuous Exposure Temperature, Power Off 700 °C Insulation Material Magnesium Oxide Sheath Material 321 Stainless Steel Area Classification Non-Hazardous; Hazardous

Table 1/1		
Catalog Number	Nominal Resistance @ 20°C	Outer Diameter
HSQ1M1000	1000 Ω/km	3.9 mm
HSQ1M10K	10000 Ω/km	3.2 mm
HSQ1M160	160 Ω/km	6.5 mm
HSQ1M1600	1600 Ω/km	3.6 mm
HSQ1M250	250 Ω/km	5.3 mm
HSQ1M2500	2500 Ω/km	3.4 mm
HSQ1M400	400 Ω/km	4.7 mm
HSQ1M4000	4000 Ω/km	3.2 mm
HSQ1M630	630 Ω/km	4.3 mm
HSQ1M6300	6300 Ω/km	3.2 mm

North America

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com



Our powerful portfolio of brands: **nVent.com** CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2021 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.