

XL-TRACE LOW SMOKE ZERO HALOGEN SELF-REGULATING HEATING CABLE



nVent RAYCHEM XL-Trace self-regulating trace heating cables provide energy efficient and easy to use solutions for pipe freeze protection and flow maintenance in grease waste lines. Developed with low smoke zero halogen (LSZH) materials, to ensure the safest solution for modern building design.

FEATURES & BENEFITS

Unparalleled safety, low smoke zero halogen construction: up to 90% less smoke emissions and improved self-extinguishing properties

Simple to design: long circuit lengths to 215 m, for fewer power connections and faster installation

Easy to install: highly flexible cable, cut to length, meter marks, fast RayClic cold connection system

Energy efficient and safe: self-regulating cable, advanced energy saving controls, major savings when used with proportional ambient sensing controller (PASC), no cable overheating possible, low smoke zero halogen

Reliable during long life: 10 year product warranty available, UV resistant, colorfast, maintenance free

SPECIFICATIONS

Supply Voltage 220 – 240 V

Outer Jacket Material Low Smoke Zero Halogen

Nominal Width 13.8 mm

Nominal Thickness 6.8 mm

Ground Path Type Braid

Min Installation Temperature -40 °C

Table 1/1

Catalog Number	Item Name	Nominal Power Output @ 5°C, 230V	Max Circuit Length	Color
P000002113	10XL2-ZH	10 W/m	215 m	Plum
P000002114	15XL2-ZH	15 W/m	160 m	Green
P000002115	26XL2-ZH	26 W/m	135 m	Blue
P000002116	31XL2-ZH	31 W/m	118 m	Purple

Circuit Lengths are based on a 20 A C-Type characteristic circuit protection device, Power on at +5 °C.

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER