

Identification Solutions

Wire and Cable Identification

HLX-NEL

Low Fire Hazard Cable Markers

HLX-NEL cable markers are designed to offer flexibility when it comes to wire and cable identification. Manufactured from the same Low Fire Hazard, UV stabilised material as HLX, with the difference being that it is assembled in a Narrow Edge Leading (NEL) format. Ideal for applications where low fire hazard characteristics (low smoke, low toxicity and low flammability) and UV protection are critical. Applied using cable ties, HLX-NEL cable markers give the ability to identify large diameter wire and cable, as well as post connector installation.

FEATURES AND BENEFITS

- Thermal transfer printable
- Excellent resistance to burning - Oxygen Index 39%
- Zero Halogen
- Low toxic fumes
- Low Smoke
- Self-extinguishing
- Recommended for use where combustion of products may endanger personnel or delicate electronics at risk
- Resistant to key industrial and rail fluids
- Ideal for low volume applications
- Cost effective identification solution
- Ideal for pre or post termination assembly

INDUSTRY



AVAILABLE OPTIONS

| | | |
|------------------|--|--------|
| Standard Colours | White | Yellow |
| Ordering Code | WE | YW |
| Format | TS | |
| | Thermal transfer (reel/ single sided) | |

(*Minimum quantity and lead time applies to non-standard colours)



Temperature Rating

Operating Temperature range -40°C to 105°C
(-40°F to 221°F)

Specifications and Approvals

EN45545-2 R22/R23/R24 HL3
MIL-STD-202 Method 215
NF F 16-101 Classification A1
London Underground 1-085 A3
BS6853 Vehicle cat 1a
SAE AS5942

Recommended Hardware and Software

Printer: T200-IDENT / TE3112 / TE3124
Ribbon: 1966-RIBBON
Software: WinTotal v6

For More information

Technical Datasheet: TTDS-134
Product Specification Sheet: RW-2529

Identification Solutions

Wire and Cable Identification

ORDERING INFORMATION

| Ordering Description | Part Number | Pack Size | Colour | Markers across | Marker Width | | Marker Height | | Printable Area (W x H) | |
|----------------------|-------------|-----------|--------|----------------|--------------|--------|---------------|--------|------------------------|--------------|
| | | pc | | | mm | Inches | mm | Inches | mm | Inches |
| HLX125YW2NEL60S | CC0110-000 | 200 | Yellow | 2 | 80.0 | 3.15 | 12.5 | 0.490 | 60.0 x 10.5 | 12.35 x 0.40 |
| HLX125WE2NEL60S | CC0111-000 | 200 | White | 2 | 80.0 | 3.15 | 12.5 | 0.490 | 60.0 x 10.5 | 12.35 x 0.40 |
| HLX125YW4NEL60S | CC0109-000 | 200 | Yellow | 4 | 80.0 | 3.15 | 12.5 | 0.490 | 60.0 x 10.5 | 12.35 x 0.40 |
| HLX125WE4NEL60S | CC0112-000 | 200 | White | 4 | 80.0 | 3.15 | 12.5 | 0.490 | 60.0 x 10.5 | 12.35 x 0.40 |

ORDERING DESCRIPTION SYSTEM

