

Deltec cable support system

2-piece reusable attachment straps



Characteristics

- Heavy-duty lashing ties, in cut lengths with pre-assembled heads
- The strap is made of UV-resistant Polypropylene, ideal for applications where chemical resistance is important
- Extremely robust (670N)
- Easily releasable & reusable
- 2 types of head:
 - type A: no mounting hole,
 - type B: with mounting hole
- Typical applications: Indoor and outdoor fastening of cables, pipes and other parts in industry, shipbuilding, chemical industry etc

- Cat. n°. 696-41563: strap on reel of 300 meter, UV resistant polypropylene
- Cat. n°. 696-41562: separate head (without fixing hole), polyamide 6.6 UV resistant

Technical information

- Material - tie : weatherable Polypropylene
- Material - head : polyamide 6.6
- Temperature range:
 - strap: -55°C to +110°C (-67°F to +230°F)
 - head: -40°C to +85°C (-40°F to +185°F)
- Flammability rating: UL 94 V-2
- Colour: Black
- Halogen free

Releasable 2-piece lashing ties, pre-assembled version

| Cat. n°. | ANSI UL94 Flame rating | Wire bundle dia. | | Length L | | Width W | | Mounting hole diameter | | Tensile strength | | Std. pkg. [pcs] |
|--|------------------------------|------------------|--------------|-------------|-------|------------|-------|---------------------------|-------|---------------------|-----|--------------------|
| | | [mm] | [in.] | [mm] | [in.] | [mm] | [in.] | [mm] | [in.] | [lb] | [N] | |
| Weather-resistant polypropylene hanger lashing tie (Releasable) | | | | | | | | | | | | |
| TY53418PX | UL 94 V-2 | 45 - 127 | 1.77 - 5 | 457 | 17.99 | 13.2 | 0.52 | 6.9 | 0,27 | 150 | 670 | 25 |
| Weather-Resistant polypropylene lashing tie (Releasable) | | | | | | | | | | | | |
| TY5418PX | UL 94 V-2 | 45 - 127 | 1.77 - 5 | 457 | 17.99 | 13.2 | 0.52 | - | - | 150 | 670 | 25 |
| TY5424PX | UL 94 V-2 | 10 - 178 | 0.39 - 7.01 | 610 | 24.02 | 13.2 | 0.52 | - | - | 150 | 670 | 25 |
| TY5442PX | UL 94 V-2 | 10 - 305 | 0.39 - 12.01 | 1.067 | 42.01 | 13.2 | 0.52 | - | - | 150 | 670 | 10 |
| TY5460PX | UL 94 V-2 | 10 - 457 | 0.39 - 17.99 | 1.524 | 60 | 13.2 | 0.52 | - | - | 150 | 670 | 10 |

Description of Cat. n°. structure: see page C13



Description of materials and properties: see pages C132 to C144

Releasable 2-piece lashing ties on reel with separate heads


| Cat. n°. | ANSI UL94 Flame rating | Max. wire bundle dia. | | Length L | | Width W | | Tensile strength | | Std. pkg. [pcs] |
|-----------|------------------------------|-----------------------|-------|-------------|-------|------------|-------|---------------------|-----|--------------------|
| | | [mm] | [in.] | [mm] | [in.] | [mm] | [in.] | [lb] | [N] | |
| 696-41562 | V-2 | - | - | - | - | - | - | 150 | 670 | 200 |
| 696-41563 | V-2 | 45 | 1.8 | 300 | 1,000 | 13.2 | 0.5 | 150 | 670 | 1 |

Diagrams



TY54XXPX



696-41563



TY53418PX



696-41562

