


# Ty-Fast®

## All-plastic ties Special ties

Thomas & Betts has developed a range of special Ty-Fast® cable ties, having the same main characteristics as the standard ties (see page 36), plus a few additional features, to provide an appropriate and elegant solution to some very specific applications. These special ties are described hereafter.



## All-plastic ties Special releasable ties



### Technical Information

Material	Polyamide 6.6
Temperature range	-40°C to +85°C
Colour	Natural or UV-resistant black (see table)
Flammability rating	UL 94 V-2
Other properties	UV-resistant (black) Halogen free, Silicone free

### Ordering Information

PRODUCT REF.	COLOUR	LENGTH L [mm]	WIDTH W [mm]	BUNDLE DIAMETER MAX. [mm]	MINIMUM TENSILE STRENGTH [N]	QUANTITY [pieces]	TOOLING
L-5-50R-0-C	UV-resistant black	150	7.5	32	220	100	WT3D ERG297 L-500-EU
L-5-50R-9-C	natural	150	7.5	32	220	100	
L-8-50R-0-C	UV-resistant black	198	7.5	51	220	100	
L-8-50R-9-C	natural	198	7.5	51	220	100	
L-10-50R-0-C	UV-resistant black	298	7.5	76	220	100	
L-10-50R-9-C	natural	298	7.5	76	220	100	

For tooling specifications see pages 92 to 99