

GENERAL USE FASTENER

VELCRO® Brand Hook & Loop Closure. Medium profile.
Adhesive designed for a wide number of substrates such as aluminum, stainless steel, glass, plywood and polyester. Adhesive is not suitable for polyethylene, polypropylene or vinyl-PVC. Medium adhesive temperature resistance. Medium tack adhesion.



CLOSURE INFORMATION		
	MATERIAL	Polyamide
	CYCLE LIFE	High
	PEEL	1.75 N/cm
	SHEAR	9.5 N/cm ²
	TENSION	4.5 N/cm ²
	ADHESIVE OPERATING TEMPERATURE	-15°C to +90°C

ADHESIVE SUBSTRATE COMPATIBILITY	
Aluminium Adonized	✓
Glass	✓
Painted Wallboard	✓
Plywood	✓
Polyester	✓
Polyethylene	✓
Polypropylene	✓
Stainless Steel	✓
Vinyl	✗
Formica (Polished Side)	✓
Cardboard	✓
Polyacrylic	✓
Fabrics	✓

✓ Recommended ✓ Good ✗ Not Recommended

REFERENCE	EAN CODE	CONTENT	WIDTH	COLOUR	ADHESIVE	QUANTITY PER SHIPPING BOX	APPLICATION METHOD
VEL-PS20002	8412355200028	5 meters of Hook Tape 5 meters of Loop Tape	20mm	■	✓	5	Stick, staple, nail, screw
VEL-PS20003	8412355200035	5 meters of Hook Tape 5 meters of Loop Tape	20mm	□	✓	5	Stick, staple, nail, screw
VEL-PS20006	8412355200066	5 meters of Hook Tape 5 meters of Loop Tape	50mm	■	✓	5	Stick, staple, nail, screw
VEL-PS20007	8412355200073	5 meters of Hook Tape 5 meters of Loop Tape	50mm	□	✓	5	Stick, staple, nail, screw
VEL-PS20000	8412355200004	25 meters of Hook Tape 25 meters of Loop Tape	20mm	■	✓	6	Stick, staple, nail, screw
VEL-PS20001	8412355200011	25 meters of Hook Tape 25 meters of Loop Tape	20mm	□	✓	6	Stick, staple, nail, screw
VEL-PS20004	8412355200042	25 meters of Hook Tape 25 meters of Loop Tape	50mm	■	✓	5	Stick, staple, nail, screw
VEL-PS20005	8412355200059	25 meters of Hook Tape 25 meters of Loop Tape	50mm	□	✓	5	Stick, staple, nail, screw

ADHESIVE RECOMMENDATIONS OF USE

Ideal temperature from 18°C to 20°C
Relative humidity from 40% to 60%

Clean the surface

Remove paper and press

Adhesive reaches maximum performance after 24 hours