

Special ties with steel locking barb

Blind mounting cable ties



Characteristics

- Suitable for hard-to-reach areas
- Fast hidden mounting on walls and vehicle chassis
- Twist off the locking head
- Pull the tie end through the fastening hole
- Place locking head on tie end
- Pull tight and cut off excess
- In the locked state, head neatly covers the mounting hole

Technical information

- Material - Molding: Polyamide 6.6
- Material - Locking barb: 316 grade stainless steel
- Temperature range: -40°C to +85°C
- Color: Natural or UV-resistant black
- Flammability rating: UL 94 V-2
- Other properties: UV-resistant (black), Halogen free, Silicone free

Blind mounting cable ties



Product code	GID No.	Color	Bundle ø from ... to [mm]	Diameter of mounting hole [mm]	Length L [mm]	Width W [mm]	Min. tensile strength [N]	Quantity [pieces]
Standard pack size								
TYG534M	7TCG009520R0080	Natural	2 - 32	6.4 - 7.0	160	3.6	180	100
TYG534MX	7TCG009520R0081	UV-resistant black	2 - 32	6.4 - 7.0	160	3.6	180	100
Bulk pack size								
TYG34M	7TCG009520R0078	Natural	2 - 32	6.4 - 7.0	160	3.6	180	1000
TYG34MX	7TCG009520R0079	UV-resistant black	2 - 32	6.4 - 7.0	160	3.6	180	1000

Description of product code structure: see page 13.

Description of materials and properties: see pages 140 to 155.

For tooling specifications: see pages 130 to 139.

Tooling



ERG50

For use with 4.8mm (220N) cable ties. See page 132.

Dimensions

