

## Special all-plastic cable ties

Standard and releasable panel mounting cable ties



### Characteristics

- Fastening and clip-mounting in one, both fastens and clip mounts
- Fast pre- or on-site-assembly for a range of panel thickness up to 2,7mm
- Fast and secure clip-mounting
- For use in 6,35mm mounting hole
- Product codes containing xxx-PMR-xxx are releasable
- Offered in Europe only

### Technical information

- Material: Polyamide 6.6
- Temperature range: -40°C to +85°C
- Color: Natural or UV-resistant black
- Flammability rating: UL 94 V-2
- Other properties: UV-resistant (black), Halogen free, Silicone free

### Standard and releasable panel mounting cable ties

Product code	GID No.	Bundle ø from ... to [mm]	Color	Length L [mm]	Width W [mm]	Min. tensile strength [N]	Quantity [pieces]
<b>Standard panel mounting ties</b>							
L-5-50PM-0-C*	7TAG054980R0640	2 - 25	UV-resistant black	147	4,8	220	100
L-5-50PM-9-D*	7TAG054710R0001	2 - 25	natural	147	4,8	220	500
L-7-50PM-0-C	7TAG054710R0004	2 - 44	UV-resistant black	208	4,8	220	100
L-7-50PM-9-C	7TAG054710R0005	2 - 44	natural	208	4,8	220	100
<b>Releasable panel mounting ties</b>							
L-5-50PMR-0-C*	7TAG054710R0002	2 - 25	UV-resistant black	147	4,8	220	100

Description of materials and properties: see pages 144 to 159.  
For tooling specifications: see pages 136 to 143.

### Tooling



**ERG50**  
For use with 4,8mm  
(220N) cable ties.  
See page 136.



**ERG120**  
For use with 4,8mm  
(220N) cable ties.  
See page 136.

### Dimensions

