



The robust, efficient and flexible design of the EuroTug makes it one of the best vessels for anchor handling, dredging support and long distance towages. The EuroTug can be adapted to perfectly fit any project within a short time.

GENERAL	
IMO NR.	9571208
CALL SIGN	ZDKE9
HOME PORT	Aalst
CLASSIFICATION	Bureau Veritas  HULL • MACH AUT UMS Unrestricted Navigation

Neptun 11 | Long Distance Towages

DIMENSIONS	
LENGTH O.A.	36,00 meters
BEAM/WIDTH	10.40 meters
DEPTH AT SIDE	5,00 meters
DRAFT MIN/MAX	3,80- 4,15 meters
AIR DRAFT	17 meters
GROSS TONNAGE	459 GT
NET TONNAGE	137 NT
DECK CARGO CAP.	6x 1 TEU, 90 tons
CLEAR DECK AREA	120 m²
CARGO DECK LOAD	5 tons per m²
TANK CAPACITIES / TRANSFER	
FUEL OIL	305.000 liters
FRESH WATER	100.000 liters
FRESH WATER GENERATOR	2,5 m³ / day
TRANSFER OF FUEL OIL	50 m³ / hr
TRANSFER OF FRESH WATER	20 m³ / hr
ACCOMMODATION	
FACILITIES	Airconditioned, 9 berths

MACHINERY / PERFORMANCES	
BOLLARD PULL	42,8 tons
MAX. SPEED	12,0 knots
SAILING RADIUS WITHOUT TOW	14.000 miles
SAILING RADIUS WITH TOW	7.000 miles
MAIN ENGINES	2x Cummins KTA-50-M2
TOTAL OUTPUT	2.388 kW = 3.244 BHP
PROPULSION	Twin fixed propellers in nozzles
BOW THRUSTER	320 kW, van Ballegooy
GENERATOR SETS	2x Cummis AQM11-D(M) 1x Cummins 6CTA8.3-D(M)
GENERATOR POWER	2x 240 kW + 1x 136 kW / 400 V
HYDRAULIC POWERPACK	ME HPU-090426 / 2x 30 kW
DECK LAY-OUT	
WINCH	ME Double Drum Waterfall
ANCHOR HANDLING	Pull Force 50T, Holding F. 100T
TOWING DRUM	Pull Force 50T, Holding F. 100T
TOW WIRES	2x 800 meters
TOW WIRES DIAMETER	48 milimeters
TUGGERWINCH	5 tons
TOWING PINS	2x SWL 200 ton
WIRE CATCHER	2 x SWL 200 ton
STERN CATCHER	SWL 200 ton
MAIN MARINE DECK CRANE	EFFER 275m SWL 1.785 ton op 12.22m
MAXIMUM LIFT CAPACITY	See next page

